


BonusPRO Heavy duty sponge scourer 10/1 B520

BRAND, PRODUCT NUMBER AND NAME	BONUS	B520	BONUSPRO HEAVY DUTY SPONGE SCOURER 10/1
TARIC	3924900090		
PRODUCER/DISTRIBUTOR	Bonus Kft. 7800 Siklós, Ipartelepi út 2., Hungary +36 1 770 7000 info@bonus-hungary.com		
CERTIFICATES	MSZ EN ISO 9001:2015, MSZ EN ISO 14001:2015, MSZ 28001:2008		
STORAGE	Store in a dry, clean place. Keep away from fire and direct sunlight.		
PRODUCT PACKAGING	30 mikron thick, mirror-printed BOPP foil		
OUTER CASE	Recyclable, FC243-55 LDPE bag and foil		
COMPOSITION	20 kg/m ³ polyurethane foam, 550g/m ² non-scratch felt		
TRADEMARK	Made in Hungary trademark, issued by Magyar Termék Nonprofit Kft. On 03.06.2013. Certificate number: 72/2013 / MTA		
PRESS KIT	https://img.bonus-hungary.com/products/B520/B520.zip		
WEBPAGE	https://en.bonuscleaningproducts.com/products/heavy-duty-sponge-scourer/		


LOGISTICS DETAILS	1x PIECE	1x PACKAGE	 OUTER CASE	 PALETTE
		SALES UNIT	ORDER UNIT	
PIECES <i>UNITS</i>	1 PIECE	10 PIECE	50 PACKAGE	400 PACKAGE
NET WEIGHT <i>GROSS WEIGHT</i>	15g	140g 146g	2,8kg 3,0kg	23kg
DIMENSIONS 	13,5×8,5×4cm	13,5×36×8,5cm	44×55×38cm	120×80×230cm
EAN-13	-	5996306052520	5997844302078	-

SPONGE COMPOSITION AND PROPERTIES	UNIT	TEST PROCEDURE	VALUE
NOMINAL FOAM DENSITY	kg/m ³	PN-EN ISO 845: 2000	17 - 19
NOMINAL HARDNESS CLD (40%)	kPa	PN-EN ISO 3386-1: 2000	2,50 - 3,35
RESISTANCE MINIMUM	%	PN-EN ISO 8307: 2000	35
COMPRESSION (50%) MAXIMUM	%	PN-EN ISO 1856: 2004	7
TENSILE STRENGTH MINIMUM	kPa	PN-EN ISO 1798: 2001	80
TENSION STRENGTH MINIMUM	%	PN-EN ISO 1798: 2001	150
CERTIFICATION	<ol style="list-style-type: none"> Oeko-Tex Certificate Standard 100, Kl. I ÉMI-TÜV Dissolution test R-1349209/1 		
COMPOSITION	Flexible polyether-polyurethane foam block made with Maxfoam or Novaflex® process.		

SCOURER LAYER INGREDIENTS	
COMPOSITION	POLYESTER AND POLYAMIDE FIBERS
BINDING RESIN	VINYL-ACRYLIC RESIN
SCOURING MATERIAL	MINERAL GRAINS
COLORANTS	NATURAL – NON-TOXIC
USAGE	HOUSEHOLD
ADDITIVES	DOES NOT CONTAIN

SCOURER LAYER PROPERTIES	TOLERANCE	VALUE	UNIT
WEIGHT	± 5%	550	g/m ²
THICKNESS	± 1 mm	6,5	mm

SCOURER LAYER PERFORMANCE	TOLERANCE	VALUE	UNIT
TENSION STRENGTH Y DIRECTION	± 4%	115	N/cm ²
TENSION STRENGTH X DIRECTION	± 4%	130	N/cm ²
SCOURING EFFECT		≥270	mg

MADE BY	APPROVED
SÁGI NORBERT 2022.05.04. 	BOTOS ANDREJ 2022.05.04. 